



## **(Teak Oil Data Sheet)**

- **Product Information:**

1. Product Name: Teak Oil
2. Product Code: WTO/001
3. Manufacturer: Woody Industrials
4. Description: Protective oil for teak and hardwoods

- **Chemical Properties:**

1. Composition: Mixture of mineral oils, waxes, linseed oil, and additives
2. Density: 0.92-0.95 g/cm<sup>3</sup>
3. Viscosity: 100-200 cSt at 20°C
4. Flash Point: 230-250°F (110-121°C)
5. pH: 7-8

- **Safety Information:**

1. Hazard Statements: H400, H410
2. Precautionary Statements: P273, P391
3. First Aid: Skin contact: wash with soap and water. Eye contact: flush with water.
4. NFPA Rating: Health: 1, Flammability: 2, Reactivity: 0

- **Physical Properties:**

1. Appearance: Yellow golden liquid
2. Odor: Mild, characteristic
3. Solubility: Insoluble in water
4. Boiling Point: 300-320°F (149-160°C)

- **Environmental Information:**

1. Biodegradability: Biodegradable
2. VOC (Volatile Organic Compound): 450 g/L
3. Disposal: Dispose according to local regulations.

- **Application Instructions**

1. Surface Preparation: Clean and dry the surface.
2. Application: Apply evenly with a cloth or brush.
3. Drying Time: 2-4 hours.
4. Recoat: As needed.

Address: 41 Heliopolis Gardens, Sheraton Heliopolis, El Nozha, Cairo, Egypt.

Cell: +2(010) 14481448 +2(011) 20182015

Social Media: woody Web: [www.woodyegy.com](http://www.woodyegy.com)



- **Storage and Shelf Life:**

1. Storage: Store in a cool, dry place.
2. Shelf Life: 2 years from manufacturing date.

- **Additional Information:**

1. Test Reports: Available upon request.
2. Transportation Information: Shipping, handling guidelines.
3. Warranty: Manufacturer's warranty.

- **Note:**

The information provided is accurate to the best of our knowledge and belief. However, we make warranty, expressed or implied if needed.