



## FA 2490

Diagonally braided packing with acrylic fibre lubricated with PTFE .

P bar	V m/s	pH	T°C
100	1,5	2 ÷ 12	-100 / +250
80	2		
50	15		



### APPLICATIONS

Centrifugal pumps, alternatives, valves, agitators and unsafe applications.



## FR 2470

Braided packing with ramie threads impregnated with lubricating PTFE.

P bar	V m/s	pH	T°C
60	1	4 ÷ 10	-50 / +250
40	3		
20	10		



### APPLICATIONS

Centrifugal pumps, alternatives, valves, agitators and unsafe applications.



## FK 6200

Braided diagonal gasket with phenolic fibers, lubricated with graphite dispersion and lubricants.

P bar	V m/s	pH	T°C
-	-	1 ÷ 12	-50 / +250
250	5		
100	20		



### APPLICATIONS

Centrifugal pumps, agitators and unsafe applications. Good chemical resistance and good mechanical resistance. Good thermal conductivity

## Base high performance synthetic fibers



## KT 30410

Diagonal braided packing with pure PTFE expanded and reinforced at the corners with aramid fibers.

P bar	V m/s	pH	T°C
500	3	3 ÷ 12	-100 / +280
300	4		
--	10		



### APPLICATIONS

Centrifugal pumps, alternatives, agitators and autoclaves. Recommended for abrasive fluids. Good chemical resistance Good mechanical resistance