555 CASE SERIES



555 case series

Handy, enclosed tape measure made of impact resistant plastic.

Tape width 10 mm



BRASS FRAMES

Brass frames for steel tapes (top picture)

Brass frame with plumb bob, can be certified (bottom picture)





Overview of tape options

High etched 13 mm



This is how your Article N° could look like:

309 01 1 010 A F



High etched stainless steel tape





Туре	Frame size	Graduation number	Length meter	Measurement commencement	Tape commencement	
309	01	X	010	Х	X	
309	01	Χ	015	Χ	Х	
309	01	Х	020	X	Χ	
309	02	Χ	025	Χ	Х	
309	02	X	030	X	Χ	
309	02	X	050	X	X	



Туре	Frame size	Graduation number	Length meter	Measurement commencement	Tape commencement	
309	03	Х	050	Х	Х	
309	04	X	100	X	X	

STANDARD



Туре	Frame size	Graduation number	Length meter	Measurement commencement	Tape commencement	
509	01	Х	010	Х	Х	
509	01	Χ	015	Χ	Χ	
509	01	X	020	X	Χ	
509	02	Χ	025	Χ	Χ	
509	02	Х	030	Х	Х	
509	02	Χ	050	Χ	Χ	



Туре	Frame size	Graduation number	Length meter	Measurement commencement	Tape commencement	
509	03	X	050	X	X	
509	04	Х	100	Х	Х	

Brass frame series



weight 476 is included, please see page 39 for description, can be calibrated

Туре	Frame size	Graduation number	Length meter	Measurement commencement	Tape commencement	
309	12	4	010	L	476	
309	12	4	015	L	476	
309	12	4	020	L	476	
309	12	4	025	L	476	
309	12	4	030	L	476	
309	12	4	050	L	476	

Please choose numbers and capital letters of desired tape features to create your Article N°.

Gr	aduations									
1	(cm)	1	I	ı	I	<mark>0</mark> 60	I	1	ı	
4	(mm)				 59	0 6061				ĮII
5	(mm/inch) 25% surch			1111 1111 58	59	0 6061//	ןייין סייין	11111 2 F	ilili f	11

Me	easurement commencements
Α	
В	O ************************************
С	Please order weight seperately, see p.39 for model variants
L	



Recommended Use

	→	—		→	—
			— E		_
		NAOZI	— HONTAIN		
	030	080	030	030	080
Tape Version:	Steel, lacquered white, printed graduation	Steel, lacquered yellow, printed graduation, Polyamide coating – "ISOLAN"	Stainless steel, printed graduation, "PONTARIT"	Stainless steel, etched graduation	Fiberglass reinforced plastic, printed graduation
Characteristics:					
Stainless	+	++	+++	+++	+++
Acid proof		+		+++	
Oil resistant				+++	
Non-conductive (insulated)					+++
Unbreakable/flexible	+	++	++	++	+++
Wear resistant	++	+++	+	++	+
Readability	+++	+++	++	+	+++
Recommended use:	multipurpose	multipurpose, tough conditions	wet conditions	especially demanding conditions	mulitpurpose, less demanding conditions
Equipment options:					
Graduation	cm, cm/cm, mm, mm/inch	cm, cm/cm, mm, mm/inch	cm, cm/cm, mm, mm/inch	cm, cm/cm, mm, mm/inch	cm, cm/cm, cm/inch
Lengths	10 to 100 m	10 to 100 m	10 to 100 m	10 to 100 m	10 to 100 m
Measurement commence	A, B, C, L	A, B, C, L	A, B, C, L	A, B, C, L	A, B, C
Tape commencements	all	all	all	all	all, but not with FLEXTOP
Accuracy:					
EC class	II, (I possible)	II, (I possible)	II, (I possible)	II, (I possible)	graduation on one side II graduation on one side III
Suitability for calibration	all versions of A and B, CH, L30	all versions of A and B, CH, L30	all versions of A and B, CH, L30	all versions of A and B, CH, L30, L476	all versions of A and B, CH





Weight 11 Brass, cylindrical, no graduation, length 190 mm, diameter 24 mm, weight 500 g (can be removed

from the tape)

Article N°. 340 00 11



Weight 18

brass cylindrical, engraved mm-scale, length 113 mm, diameter 25 mm, weight 400 g (cannot be removed from the tape)





Weight 16

Stainless steel cylindrical, engraved mm scale on one and inch scale on the other side, length 113 mm, diameter 25 mm, weight 400 g (cannot be removed from the tape)





Weight 14

Brass cylindrical, engraved mm scale on one and inch scale on the other side, length 80 mm, diameter 24 mm, weight 300 g (cannot be removed from the tape)

Article N°. 340 02 14



Weight 10

Brass cylindrical, engraved mm scale on one and inch scale on the other side, length 89 mm, diameter 24 mm, weight 300 g (can be removed from the tape)

Article N°. 340 02 10



Weight 30

Brass cylindrical, torpedo-shaped ends, mm scale engraved on one side, length 153 mm, diameter 30 mm, weight 700 g (cannot be removed from the tape)

C € Article N°.340 01 30



Weight 31 according to IPM Standard

Brass cylindrical, torpedo-shaped ends, mm scale engraved on one side, length 156 mm, diameter 30 mm, weight 700 g (can be removed from the tape)

Article N°. 340 01 31 IPM



Weight 476

Brass cylindrical, length 100 mm, diameter 45 mm, weight 660 g (cannot be removed from the tape)

CE see page 46

Custom made measuring tapes

As an example – tapes with adhesive back and graduation from right to left.

We would be pleased to produce custom tapes for your individual needs. Almost anything is possible – just ask!